



# RAPID DEPLOY KIT

ENABLED BY STARLINK

## ALL-IN-ONE, PORTABLE COMMUNICATION

In time-critical situations, reliable connectivity is essential. Speedcast's Rapid Deploy Kit provides fast, low-latency broadband using Starlink Low Earth Orbit (LEO) technology, packaged for rapid transport and deployment in the field.

The Rapid Deploy Kit is designed to support either Starlink Mini or Starlink Performance (Gen 3), housed in rugged, purpose-built Caseman travel cases\*. This flexibility makes it ideal for first responders, mobile command units, and teams operating in remote or temporary environments across sectors such as emergency services, media, mining, energy, government, and NGOs.

\*Starlink terminals are sold separately.



### PORTABLE & RUGGED

- Purpose-built rugged carrying cases designed specifically for Starlink Mini or Starlink Performance (Gen 3) (Starlink kits sold separately)
- Optimized for rapid mobilization to disaster zones and remote locations worldwide
- Durable, waterproof, and dust-tight construction to withstand harsh field conditions



### EASY TO DEPLOY

- Designed for single-person setup
- Under 15-minute assembly time with minimal maintenance
- Supports quick transition from transport to live operation in the field



### GLOBAL

- The Rapid Deploy Kit provides high speed internet services from anywhere in the world
- High-speed broadband connectivity delivered over Low Earth Orbit (LEO) satellites
- Upon ordering, the Rapid Deploy Kit is delivered to your doorstep

## RUGGED CASE OPTIONS

### FOR STARLINK MINI (KIT SOLD SEPARATELY)

- Compact, lightweight solution ideal for highly mobile teams and rapid deployment scenarios
- Waterproof and dust-tight construction
- Ultra high-strength polypropylene copolymer resin
- Lightweight, compact design for maximum portability
- Exterior dimensions: 18.25 × 14 × 7 in
- Loaded weight: 15 lb



### FOR STARLINK PERFORMANCE (GEN 3) (KIT SOLD SEPARATELY)

- High-capacity option suited for mission-critical operations requiring enhanced throughput
- Wheeled case with pull handle for easier transport
- Custom cable pass-through and integrated Ethernet port
- Designed to accommodate Starlink Performance (Gen 3) dish, router, power supply, and cables
- Exterior dimensions: 28.5 × 20.5 × 13.5 in
- Loaded weight: 35 lb